# GUIDE FLAMMABLE LIQUIDS - CORROSIVE

# POTENTIAL HAZARDS

# FIRE OR EXPLOSION

- · Flammable/combustible material.
- · May be ignited by heat, sparks or flames.
- · Vapors may form explosive mixtures with air.
- · Vapors may travel to source of ignition and flash back.
- Most vapors are heavier than air. They will spread along the ground and collect in low or confined areas (sewers, basements, tanks, etc.).
- · Vapor explosion hazard indoors, outdoors or in sewers.
- Those substances designated with a (P) may polymerize explosively when heated or involved in a fire.
- Runoff to sewer may create fire or explosion hazard.
- · Containers may explode when heated.
- Many liquids will float on water.

### HEALTH

- May cause toxic effects if inhaled or ingested.
- · Contact with substance may cause severe burns to skin and eyes.
- Fire will produce irritating, corrosive and/or toxic gases.
- · Vapors may cause dizziness or asphyxiation.
- · Runoff from fire control or dilution water may cause environmental contamination.

# **PUBLIC SAFETY**

- CALL 911. Then call emergency response telephone number on shipping paper. If shipping paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.
- · Keep unauthorized personnel away.
- Stay upwind, uphill and/or upstream.
- · Ventilate closed spaces before entering, but only if properly trained and equipped.

# PROTECTIVE CLOTHING

- · Wear positive pressure self-contained breathing apparatus (SCBA).
- Wear chemical protective clothing that is specifically recommended by the manufacturer when there is NO RISK OF FIRE.
- · Structural firefighters' protective clothing provides thermal protection but only limited chemical protection.

# **EVACUATION**

### Immediate precautionary measure

• Isolate spill or leak area for at least 50 meters (150 feet) in all directions.

#### Spill

- For highlighted materials: see Table 1 Initial Isolation and Protective Action Distances.
- For non-highlighted materials: increase the immediate precautionary measure distance, in the downwind direction, as necessary.

#### Fire

If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.



In Canada, an Emergency Response Assistance Plan (ERAP) may be required for this product. Please consult the shipping paper and/or the ERAP Program Section (page 390).

# Page 200

# ERG 2020

# EMERGENCY RESPONSE

# FIRE

# Some of these materials may react violently with water. Small Fire

• Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

## Large Fire

- Water spray, fog or alcohol-resistant foam.
- · If it can be done safely, move undamaged containers away from the area around the fire.
- Dike runoff from fire control for later disposal.
- · Do not get water inside containers.

# Fire Involving Tanks or Car/Trailer Loads

- · Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles.
- · Cool containers with flooding quantities of water until well after fire is out.
- · Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned master stream devices or monitor nozzles; if this is impossible, withdraw
  from area and let fire burn.

# SPILL OR LEAK

- · ELIMINATE all ignition sources (no smoking, flares, sparks or flames) from immediate area.
- All equipment used when handling the product must be grounded.
- Do not touch or walk through spilled material.
- · Stop leak if you can do it without risk.
- · Prevent entry into waterways, sewers, basements or confined areas.
- A vapor-suppressing foam may be used to reduce vapors.
- · Absorb with earth, sand or other non-combustible material.
- · For hydrazine, absorb with DRY sand or inert absorbent (vermiculite or absorbent pads).
- · Use clean, non-sparking tools to collect absorbed material.

### Large Spill

- Dike far ahead of liquid spill for later disposal.
- · Water spray may reduce vapor, but may not prevent ignition in closed spaces.

# FIRST AID

- Call 911 or emergency medical service.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.
- · Move victim to fresh air if it can be done safely.
- · Give artificial respiration if victim is not breathing.
- Do not perform mouth-to-mouth resuscitation if victim ingested or inhaled the substance; wash
  face and mouth before giving artificial respiration. Use a pocket mask equipped with a one-way
  valve or other proper respiratory medical device.
- Administer oxygen if breathing is difficult.
- · Remove and isolate contaminated clothing and shoes.
- · In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.
- Keep victim calm and warm.
- · Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.

# ERG 2020